

sub 122
 cont. 122
 mechanism 80 is moved in an axial direction along the X axis such that the second biasing member 104 is no longer under tension, but the first biasing member 100 is now under tension. The first end 90 of the pin 82 passes through the openings 120 and 122 of the guard rail socket 40 and through the opening 124 in the side leg 64 of the channel 60. The first biasing member 100 is compressed between a first side 43 of the guard rail socket 40 and the pin 98.

A paper entitled "Marked-up Version of the Replacement Paragraph(s)/Section(s) (37 C.F.R. 1.121(b)(1)(iii))" is attached hereto.

IN THE CLAIMS

Please amend the claims as follows:

- sub 122
 Q3
1. (Amended) A scaffold system comprising at least one first support and at least one second support and at least one locking and securing device for removably securing and locking the first support to the second support, the locking and securing device having a means for securing the first support to the second support, the securing means being movably attached to the first support and being movable between a secured position and an unsecured position with respect to the second support by using a force at a substantially coaxial center point of the securing means; and a means for locking the securing means to the

Sub 232 Contd.
first support when the securing means is in the secured position in the second support, the locking means being integrally formed with the securing means;

Cont. A3
the securing means and the locking means being rotatably moveable about a longitudinal axis extending through the securing means and being longitudinally moveable along the longitudinal axis thereby allowing the securing means to be moveable between the secured position and the unsecured position and thereby allowing the locking means to be moveable between a locked position and an unlocked position.

A4 Sub 232 Contd.
3. (Amended) The scaffold system of claim 2, wherein the securing pin is positioned at an angle with respect to the first support.

A5 Sub 232 Contd.
15. (Amended) The scaffold system of claim 14, wherein the second support defines an engagement member for engagement with the locking means when the locking means is in the locked position.

Sub 232 Contd.
A6
21. (Amended) A scaffold system comprising at least one first support and at least one second support and at least one locking and securing device for removably securing and locking the first support to the second support, the locking and securing device having a means for securing the first support to the second support, the securing means being movably attached to the first support

Sub 33 cont
and being movable between a secured position and an unsecured position with respect to the second support by using a force at a substantially coaxial center point of the securing means; and a means for locking the securing means to the first support when the securing means is in the secured position in the second support, the locking means being integrally formed with the securing means;

cont. 116
the securing means and the locking means being rotatably moveable about a longitudinal axis extending through the securing means and being longitudinally moveable along the longitudinal axis thereby allowing the securing means to be moveable between the secured position and the unsecured position and thereby allowing the locking means to be moveable between a locked position and an unlocked position;

wherein the second support includes at least one opening for receiving the securing means when the securing means is in the secured position;

wherein the first support includes a channel member for receiving a portion of the second support when the first support is secured to the second support;

wherein the channel member defines at least one opening for receiving a portion of the securing means;

further including at least one guide rail socket for receiving one end of a guide rail, the guide rail socket being adjacent and substantially parallel to the channel member; and

Sub 32
C-1

wherein the guide rail socket defines first and second openings that are in opposing sides of the guide rail socket for receiving a portion of the securing means.

Am
C-1

22. (Amended) A scaffold system comprising at least one first support and at least one second support and at least one locking and securing device for removably securing and locking the first support to the second support, the locking and securing device comprising a securing mechanism, the securing mechanism including a longitudinally extending securing pin and a handle positioned in a spaced apart and substantially coaxial centered relationship with respect to the securing pin, the securing mechanism further including a locking member positioned adjacent the handle in a spaced apart relationship to the securing pin;

the securing pin being moveable between a secured position and an unsecured position and the locking member being moveable between a locked position and an unlocked position.

Sub 32
C-1

30. (Amended) The scaffold system of claim 29, wherein the securing mechanism further includes a second biasing member coaxially positioned on one end of the securing pin in a spaced apart relationship to the first biasing spring member.

34. (Amended) A scaffold system comprising at least one first support and at least one second support and a locking and securing device for removably securing the first support to the second support, the locking and securing device comprising an engagement member and a securing mechanism having a securing pin extending in an axial direction through the engagement member,

the securing pin having a radially extending opening extending therethrough for receiving a rivet pin,

a first biasing member coaxially positioned on the securing pin between the rivet pin and a first end of the securing pin,

a second biasing member coaxially positioned on the securing pin between the rivet pin and a second end of the securing pin,

a handle operatively connected to the second end of the securing pin and in a substantially coaxial centered relationship with respect to the securing pin, and,

a locking member integrally formed with the handle.

Please add the following new claims

41. (New Claim) The scaffold system of claim 2, wherein the handle is in a plane extending through a line defined by a Y axis and the securing pin is in a plane extending through a line defined by an X axis, the securing pin and handle

sub B3
cont
being in the same plane as defined by the X and Y axes; the securing pin also being in a spaced apart and parallel relationship with an extending section of the locking member which is also in a plane defined by the X axis.

cont.
A9
42. (New Claim) The scaffold system of claim 41, further including an engaging means in a spaced apart relationship to the handle, the engaging means being in a plane extending through a line defined by a Z axis in a direction away from the X axis, wherein the Z axis is perpendicular to both the X and Y axes such that a distal end extends from the engaging means in a direction toward the handle whereby the distal end is in a second plane extending through a line defined by a second Y axis.

43. (New Claim) The scaffold system of claim 22, wherein the handle is in a plane extending through a line defined by a Y axis and the securing pin is in a plane extending through a line defined by an X axis, the securing pin and handle being in the same plane as defined by the X and Y axes; the securing pin also being in a spaced apart and parallel relationship with an extending section of the locking member which is also in a plane defined by the X axis.

44. (New Claim) The scaffold system of claim 43, further including an engaging means in a spaced apart relationship to the handle, the engaging means

Sub 37
cont.
being in a plane extending through a line defined by a Z axis in a direction away from the X axis, wherein the Z axis is perpendicular to both the X and Y axes such that a distal end extends from the engaging means in a direction toward the handle whereby the distal end is in a second plane extending through a line defined by a second Y axis.

cont.
a9
45. (New Claim) The scaffold system of claim 34, wherein the handle is in a plane extending through a line defined by a Y axis and the securing pin is in a plane extending through a line defined by an X axis, the securing pin and handle being in the same plane as defined by the X and Y axes; the securing pin also being in a spaced apart and parallel relationship with an extending section of the locking member which is also in a plane defined by the X axis.

46. (New Claim) The scaffold system of claim 45, further including an engaging means in a spaced apart relationship to the handle, the engaging means being in plane extending through a line defined by a Z axis in a direction away from the X axis, wherein the Z axis is perpendicular to both the X and Y axes such that a distal end extends from the engaging means in a direction toward the handle whereby the distal end is in a second plane extending through a line defined by a second Y axis.

Sub B37 Cont.
47. (New Claim) The scaffold system of claim 21, wherein the securing means includes a securing pin and a handle positioned in a spaced apart relationship to and at substantially the center point of the securing pin.

48. (New Claim) The scaffold system of claim 47, wherein the securing pin is positioned at an angle with respect to the first support.

Cont. A9
49. (New Claim) The scaffold system of claim 47, wherein the handle is integrally formed with the locking means.

50. (New Claim) The scaffold system of claim 47, wherein the locking means includes an engaging means for engagement with the first support when the locking means is in the locked position.

51. (New Claim) The scaffold system of claim 50, wherein the first support is operatively connected to an engagement means for engagement with the engaging means of the locking means.

52. (New Claim) The scaffold system of claim 51, wherein the securing means is positioned at an angle with respect to the engagement means and extends through an opening in the engagement means.

Sub 63 cont
53. (New Claim) The scaffold system of claim 22, wherein the securing means further includes at least one biasing means for holding the securing means in the secured position.

cont. 67
54. (New Claim) The scaffold system of claim 53, wherein the securing means further includes a second biasing means for holding the locking means in the locked position.

55. (New Claim) The scaffold system of claim 54, wherein the first biasing means and the second biasing means are coaxially positioned on the securing means.

56. (New Claim) The scaffold system of claim 55, wherein the first and second biasing means are spaced apart from one another by a rivet pin extending radially through the securing means.

57. (New Claim) The scaffold system of claim 48, wherein the rivet pin is positioned in the securing pin at substantially a midpoint along a longitudinal length of the securing means.

50 B3 cont
58. (New Claim) The scaffold system of claim 47, wherein the handle and the securing pin are at an angle with respect to each other and are in the same plane with respect to each other.

cont
a9
59. (New Claim) The scaffold system of claim 58, wherein the locking means includes an engaging means which is in a spaced apart relationship to the handle and is positioned at an angle to the handle, the engaging means and the handle each defining planes that are perpendicular to each other.

60. (New Claim) The scaffold system of claim 59, wherein the second support defines an engagement member for engagement with the locking means when the locking means is in the locked position.

61. (New Claim) The scaffold system of claim 60, wherein the engagement member is operatively connected to the first support.

62. (New Claim) The scaffold system of claim 1, wherein the securing means has no threaded portion.

63. (New Claim) The scaffold system of claim 1, wherein the locking means has no threaded portion.

64. (New Claim) The scaffold system of claim 1, wherein the securing and the locking means are secured by being rotated about one half turn.

65. (New Claim) The scaffold system of claim 1, wherein the securing means and the locking means are secured by being rotated about 160° to about 180°.

66. (New Claim) The scaffold system of claim 21, wherein the securing means has no threaded portion.

67. (New Claim) The scaffold system of claim 21, wherein the locking means has no threaded portion.

68. (New Claim) The scaffold system of claim 21, wherein the securing and the locking means are secured by being rotated about one half turn.

69. (New Claim) The scaffold system of claim 21, wherein the securing means and the locking means are secured by being rotated about 160° to about 180°.

70. (New Claim) The scaffold system of claim 22, wherein the securing mechanism has no threaded portion.

Sub B3 cont

71. (New Claim) The scaffold system of claim 22, wherein the securing mechanism is secured by being rotated about one half turn.

cont a9

72. (New Claim) The scaffold system of claim 22, wherein the securing mechanism is secured by being rotated about 160° to about 180°.

73. (New Claim) The scaffold system of claim 34, wherein the securing mechanism has no threaded portion.

74. (New Claim) The scaffold system of claim 34, wherein the securing mechanism is secured by being rotated about one half turn.

75. (New Claim) The scaffold system of claim 34, wherein the securing mechanism is secured by being rotated about 160° to about 180°.

Pursuant to 37 C.F.R. 1.121(c)(1)(ii), a paper entitled "Marked-up Version of the Amended Claim(s) (37 C.F.R. 1.121(c)(1)(ii))" is attached hereto.